
UMITATIONS



- FINISH GRADE.
- VALVE I.D. TAG WITH "MV" PRINTED ON IT.
- MASTER VALVE WIRES FROM SOLENOID (INCLUDED).
- PAIR OF WIRES, COLOR CODED DIFFERENT THAN. OTHER VALVES. REFER TO CONTROLLER SPECS
- 1 1/2" SCH 40 CONDUIT FROM CONTROLLER PER SPECS. PULL BOXES EVERY 200' AND ON EACH SIDE OF HARDSCAPES AREA.
- PVC MAINLINE PIPING PER IRRIGATION LEGEND. (PLAN SIZE)
- FILTER FABRIC PER SPECS.
- BRICK SUPPORT. (4 TOTAL/ 1 @ EA CORNER)

- JUMBO VALVE BOX WITH EXTENSION(S) PER SPECS. HEAT BRAND "MV-FS" ON LID IN 2" HIGH BLOCK LETTERS.
- 10. PRESSURE REDUCING PILOT
- 11. WATERPROOF WIRE CONNECTORS (3M DBY/DBR)
- 12. SHIELDED FLOW SENSOR WIRES TO CONTROLLER (PER CONTROLLER SPECS).
- 13. NETAFIM HYDROMETER, REFER TO LEGEND FOR MODEL NUMBER.
- 14. SCH.80 PVC MIPT ADAPTOR SIZE PER VALVE AND MAINLINE PIPING (2 REQUIRED)
- DRAINAGE NUT FOR WINTERIZATION (INCLUDED).
- 16. CONCRETE PAVER SUPPORT BLOCK.
- 17. COMPACTED 3/4" WASHED GRAVEL. 12" THICK MIN.
- 18. COMPACTED NATIVE SOIL.

NOTES TO DESIGNER:

- NO STRAIGHT PIPE UPSTREAM AND DOWNSTREAM OF HYDROMETER IS REQUIRED.
- THE INSTALLATION OF AN ISOLATION VALVE UPSTREAM OF THE HYDROMETER IS RECOMMENDED.
- ALL THREADED CONNECTIONS SHALL RECEIVE TEFLON TAPE PER TAPE MANUFACTURERS RECOMMENDATIONS.



HYDROMETER 2" FNPT PRESSURE REDUCING MANUAL ELECTRIC & NETAFIM



NOT TO SCALE